



c o n c r e a t i v i t y



# SEALING REMOVER EXTRA STRONG

## Strong liquid sealing remover

### DESCRIPTION

Isoplam® Sealing Remover Extra Strong is a strong liquid sealing remover made of a strong acids mix with methylene chloride. It can remove epoxy and lead-based coverings. It has a typical dark brown colour and is strong smelling.

### FIELDS OF USE

Isoplam® Sealing Remover Extra Strong can remove:

- Resins applied on industrial and decorative concrete floorings;
- Lead-based paints;
- Polyurethane resins.

### APPLICATION

Warning: it is recommended to try the product before use, in order to determine waiting times and the real consumption.

Protect the areas that must not be treated with polyethylene sheets. In case of nylon ribbon, it is recommended to apply it twice and to remove the first one immediately after the first coat of Sealing Remover Extra Strong.

Isoplam® Sealing Remover Extra Strong acts better when temperatures are not too high, between +10°C and +35°C.

Clean well the support and wet it.

Apply the pure product on the surface with a watering can and a broom and let it act for 3-5 minutes.

Pour some water on the surface and emulsify for some minutes with Sealing Remover Extra Strong using a monobrush or a power trowel with a polyethylene disc (the surface must not get dry).

Rinse the floor accurately with a high-pressure cleaner and a wet vacuum cleaner: every residue to dispose in tanks according to legislation.

If necessary, repeat the application.

### CONSUMPTION

The consumption varies between 0,150 Kg/m<sup>2</sup> to 0,400 Kg/m<sup>2</sup>, according to the coat and to the kind of resin to remove.

### PACKAGES AND STORAGE

Isoplam® Sealing Remover Extra Strong is supplied in plastic packages of 20 Lt.

Storage at temperatures between +10°C and +35°C in their original packages.

A slight swelling of the package is acceptable.

**ISOPLAM S.R.L.**

Via E. Mattei, 4 – Z. I. Maser (TV) – Italia Tel. (+39) 0423 925023 Fax (+39) 0423 926119 [www.isoplam.it](http://www.isoplam.it)

IDENTIFICAZIONE ISO 9001:2015 Rev. 27/07/2016



c o n c r e a t i v i t y



## WARNING

Isoplam® Sealing Remover Extra Strong is intended for professional use only: pay attention during its use.

Apply this product only in ventilated places, even with forced ventilation in case of air stagnation. Given the strong odour, we do not suggest to use it near habitations.

Do not conserve the removed paint in metallic packages: use only plastic packages.

Use proper protective garment: neoprene gloves, goggles and, in case of insufficient ventilation, wear suitable respiratory equipment (suggested filter for the mask: AX).

Pay attention to the shoes you wear: the product may attack soles, do not wear rubber boots.

Consult the security sheet before use.

## IMPORTANT:

The product Sealing Remover Extra Strong is intended for the use as indicated above. Adding any other product will impair the final result. All information contained herein is based on the best practical experiences and laboratory research. It is the customer's responsibility to determine whether the product is suitable for the intended application. The manufacturer declines all responsibility on the results due to incorrect application of its products. The product shall always be tested on a small area before full scale application. This data sheet replaces all previous data sheets. ISOPLAM reserves the right to change the data on the data sheet at any time. Sealing Remover Extra Strong is intended for professional use only. ISOPLAM provides frequent and on demand trainings for its customers. The use of ISOPLAM products without receiving the proper certification will be at the customer's own risk.